

**3M** Science.  
Applied to Life.™



## 3M™ Envision™ Print Film Series

# Stunning print films that can help you reach your sustainability goals.

The non-PVC 3M™ Envision™ Print Films are designed to deliver outstanding performance while helping you reduce your environmental footprint.

### From farm to film: 3M™ Envision™ Print Film PL50mC

To better meet your performance and sustainability needs, we've taken it one step further with 3M™ Envision™ Print Film PL50mC. It's a next generation film designed for short-term applications that require excellent print quality, conformability and removability.

Made from 47% bio-based materials,\* this 2 mil film features Comply™ and Controltac™ technologies for fast, easy and bubble-free installations. This film can be paired with recommended 3M overlaminates to create a matte or gloss finish.

\*Derived from non-food source corn.

# Find the right 3M™ Envision™ Print Film for you

Product & Description	<b>3M™ Envision™ Print Film PL50mC</b>  Made from 47% bio-based material that provides good conformability, excellent removability for short-term applications	<b>3M™ Envision™ Print Wrap Film LX/SV480mC</b>  Non-PVC film designed for excellent conformability and durability for longer-term applications  Fast, easy installation due to Controltac™ and Comply™ adhesive with ability to install in a wide temperature range	<b>3M™ Envision™ Print Film 48C</b>  Non-PVC film designed for flat surfaces such as walls or flat panels for vehicles  May be eligible for LEED credits
Conformability	Good	Excellent	Average
Film Thickness	2 mil	2 mil	3.3 mil
Removability	Removable without heat	Removable with heat	Available with removable or permanent adhesive
Applications	Vehicle, fleet, POP, temporary signage, flat or smooth surfaces	Vehicles, fleet, boats, textured or smooth walls	Interior & exterior signage, POP, indoor floor & smooth wall graphics, box trucks, trailers
Overlamine Compatability <small>*Non-PVC</small>	8518, 8519, 8520, 8548G*, 8549L*, 8550M*, 8048G*, 8050M** <small>† For interior applications only</small>	8048G*, 8050M*, 8548G*, 8549L*, 8550M*	8548G*, 8549L*, 8550M*
Fire testing results	ASTM E84, EN45545	ASTM E84, EN45545	ASTM E84, EN13501, EN45545
GREENGUARD Gold certified <small>(low emission of VOCs in indoor environments)</small>	—	Yes	Yes
 <b>3M™ MCS™ Warranty</b> — 35 years and going strong —	Eligible	Eligible	—

