



# **SAFETY FILMS**

## AGM 400 ANTI-GRAFFITI

### **IN & OUT INSTALLATION**



The AGM 400 film is a multi-layer film designes for windows that are highly exposed to graffiti and other urban deterioration.

Composed of 4 layers of 100 microns each, you only have to remove the layer when it is damaged, in order to get back a new window instantly.







**Durability:** 12 to 15 years for a vertical application in Central Europe.



Use: for all types of glass.



**Maintenance:** after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



**Storage:** 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

### **INFORMATION**

SUPPORT:	PET
THICKNESS:	4 x 100 microns
PROTECTOR:	Siliconized PET 23 microns
APPLICATION SIDE :	Internal & External
T° D'APPLICATION :	min + 5°C
STANDARDS:	EUROCLASSES
DURABILITY:	3 vears*

\*For glazing not exposed to the sun

#### **DIMENSIONS**

By roll:



1,52 x

30 m

Application Note





Video of the





#### Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

#### Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.