

## Ikonos Proficoat Canvas "Picasso" CVS 320SM

### → AVAILABLE STANDARD WIDTHS AND LENGTHS

0.914, 1.067, 1.37, 1.52 x 30 m. Other lengths on Customers' individual request.

### → PRODUCT DESCRIPTION

Ikonos Proficoat Canvas "Picasso" CVS 320SM is a premium inkjet printable substrate consisting of a polyester / cotton blend (65% polyester, 35% cotton) with a homogeneous, uniform surface.

### → APPLICATION

High quality artistic graphics and paintings reproduction.

### → PROPERTIES

Ikonos Proficoat Canvas "Picasso" CVS 320SM shows a warm-white surface, high dimensional stability and very high tear resistance. The surface is homogeneous, closed and crack-free.

### → PRINTING METHODS

Eco-solvent, solvent, latex, UV.

### → PHYSICAL FEATURES OF CANVAS "PICASSO" CVS 320SM

	<b>STANDARD NO.</b>	<b>VALUE</b>
Grammage	DIN EN ISO 536	320 g/m <sup>2</sup>
Thickness	DIN EN ISO 534	400 mic
Composition	Poly-cotton-mix	65% PES, 35% CO

After printing the ink must be perfectly dry so as to avoid any effect on the later combination with the application surface. The surface on which canvas is applied must be free of dust, grease, lubricant and any other substances which may hinder the film from adhesion. Freshly lacquered or painted surfaces should be allowed to dry for no less than three weeks. The compatibility of particular lacquers and paints should be tested by the user, prior to application on the material.

All rights reserved. All trademarks and registered trademarks are the property of their respective owners. The information included in the present publication is based upon our knowledge as well as practical experience and can be changed without prior notice. This data is displayed only in order to serve as a source of information and is given without guarantee and does not constitute a warranty. Owing to wide range of possible uses and applications, customers should independently verify the appropriateness of this material for their explicit purpose, prior to use.

**IKONOS LARGE FORMAT PRINTING MEDIA**

Polska, 45-446 Opole, ul. Gosławicka 2D

Tel.: +48 77 455 63 19 / Fax: +48 77 455 63 17