

GRADIENT

INT 120

INTERNAL APPLICATION



White gradient

DOTS PATTERN

DESCRIPTION:

INT 120 is a decorative film designed for an internal application with a white dots pattern. The full part of the film is 20cm long.



Durability: from 12 to 15 years for vertical application in central Europe.



Use: Réflectiv window films are designed for use on any type of clear normal glass.



Maintenance after 30 days: with usual cleaning solutions (non-abrasive, without ammonia...). Cleaning products that may scratch the film should be avoided.



Storage: 2 years from delivery. This film should be kept away from excessive humidity and sun rays, at temperatures below 38°C.

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice.


INFORMATION

MATERIAL:PET 23 microns
ADHESIVE:Acrylic polymer 13 gr/m²
LINER:Siliconed pet 23 microns
THICKNESS:23 microns
COLOR:White gradient
APPLICATION FACE :Internal
APPLICATION T°:min, + 5°C
FIRE RATING: B-S1, D0
STANDARDS:EUROCLASSES
WARRANTY:10 years inside*

*for glazing not exposed to the sun

DIMENSIONS

1,52 x 2,5 m
 1,52 x 5 m
 1,52 x 10 m
 1,52 x 30 m



Application Method

The glass surface to be glued on has to be free from dust, grease or other contaminants. Some specific materials such as polycarbonate can cause air bubble problems. Therefore, a compatibility test is recommended. For more precision we recommend to refer back to the application table.

Production and standards

In order to constantly improve our production we may change a product colour and manufacturing process without prior notice. Before applying our products we recommend that our users ensure that the film is suitable for the intended use and comply with current standards.