



DIGIT 150 CLING

White Gloss

Product Information

Monomeric, electrostatic PVC Film (white gloss, 150 μ) laminated on an one-sided clay-pasteboard liner (180 g/m²).

The PVC offers a high dimensional stability.

Especially designed for short-term window decoration.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

Technical Data

Carrier:	Monomeric, electrostatic PVC, (cling-film)	
Thickness:	150 μ	+/- 5 %
Adhesive:	./.	
Adhesion:	./.	
Liner:	one-sided clay-pasteboard (180 g/m ²)	
Application temperature:	+10 - +40 °C	
Temperature durability :	- 40 - +80 °C	
Outdoor durability:	6 month (unprinted film)	

Standard Dimensions

1000 mm x 50 m
1370 mm x 50 m

KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501
Fax: +39 0481 882 440

E-Mail: info@kemicasrl.it
Internet: www.kemica.it

19/11/2018

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.