



Description

Material	Self adhesive 100% polyester textile, coated on one side
Coating	White, satin coating
Properties	High stability against environmental influences Fast drying Brilliant colour reproduction No reflections on the printed surface Suitable for wall decoration
Application	Indoor: art prints and wall decoration
Durability	For medium-term use depending on the ink
Inks	Eco solvent, solvent, latex and UV curable inks

Laminating

We recommend protecting the printer surface when it is subjected to abrasion, moisture or other mechanical influences. In this case, we recommend protecting the image with an appropriate liquid lamination.

Technical Data

Fabric base	100%polyester textile, 230 g/m ² ,240 μ, satin white coating
Adhesive	Acrylic UV hot melt, water and heat high resistance, 30 g/m ²
Liner	Clay coated paper, 80 g/m ²
Final product	self adhesive 100%polyester textile, satin white coating
Weight	340 g/m ²
Peel 180° Method FTM1 (n/25 mm)	After 20 min. 1,1Newtons After 4 hours.1,1Newtons After 24 hours. 1,2Newtons

Availabilities

1020 mm - 40"

1370 mm - 54"

1520 mm - 60"

Roll length	20m (any other length can be produced under request)
--------------------	--

Storage

After printing we recommend to remove the remaining roll from the plotter and to keep the canvas in the original packaging in a cool and dry environment.

Notes

Slight colour deviations can occur from production to production.