



A NEKOOSA BRAND

GXP-850

Technical Data

Product Description – A medium tack paper application tape for vinyl graphics used in sign making and surface protection. The product is a heavyweight paper ideal for medium and large graphics and die-cuts. Thanks to the specially formulated latex pressure sensitive adhesive, the tape sticks to large areas of exposed release liners.

Product Characteristics

Construction

Backing	White translucent
Adhesive	Rubber-based
Total Thickness	152 micron

Performance

Tensile Strength (pli)	
MD	332 N/100mm
Elongation (%)	12%
Tack level	Medium

Adhesion to steel	14 N/100mm
-------------------	------------

*Adhesion PSTC-1, 1 minute on stainless steel at time of manufacture

The physical properties listed above are typical values and are not to be considered as specifications. Our suggestions for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their internal use. Nekoosa assumes no liability for claims beyond those outlined within our Limited Warranty, which includes replacement value of Nekoosa product proven defective. For full disclosure of the Limited Liability Warranty, please contact your Nekoosa representative.

Typical Uses - Excellent for pre-spaced lettering <2", medium and large-sized one piece decals and hard to lift vinyls. All purpose application tape for most sign shop applications.