

CODE: OWV-S40

NAME: Perforated Vinyl S/A 40/60

FEATURES:

There are three types perforated vinyl for different purposes from short term, economic quality to good quality for medium term advertisings and signs. And four kinds of open rates which are good for different application scenarios from 20/80, 30/70, 40/60 to 50/50. Our One-Way-Vision are competitive and covering most daily requirements.

PROPERTY

PARAMETER		VALUE
Film	Type/ Materials	Monomeric PVC
	Caliper (um)	160
	Open Rate	40%
	Finish	45@60°
	Elongation at break (%) MD/CD	210/220
	Shrinkage(mm) MD/CD FTM-14	0.30/0.24
Glue	Type/ Materials	Clear removable solvent based acrylic glue
	Thickness /um	25
	Init Tac 20min peeling (N/in) FTM-9	2.2N
	Hold: 9.8N/in ² (Hours)	48Hours
	180°Peeling (N/in) FTM-1	5.2N
Paper	Type/ Material	SPE kraft paper
	Weight (g/m ²)	160
Available size	Width	0.914/1.07/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	50m/45.72m (164'/150')
Shelf Time (Month) (20°C x 50% R.H)		12-24 Months
Applying Temperature Range °C		-10~65°C
Outdoor durability		24 Months

PRINTING INK

Solvent	Eco-Sol	UV	Latex
Y	Y		

APPLICATION

Billboard Graphic	Rigid Board Graphic	Window Graphic	Wall Graphic	Floor Graphic	Vehicle Graphic	Signs
		Y			Y	Y

NOTE: All values shown are for reference only. The mentioned data are average of test results and should not be used for the purpose of lawsuit or warranty.