

TEC MARK 3000 Series

Product Information

Monomeric PVC Film (gloss/matt, 70 μ) with clear, ecological compatible dispersion adhesive (semi-permanent), laminated on an one-sided clay-coated silicone paper liner (120 g/m²).

A perfect glossy/matt face film in addition to high flexibility and comformability makes the product suitable also for non-smooth surfaces. Especially designed for vehicle lettering, decorating of windows, signs, etc. with excellent plotting, weeding and application characteristics.

Suitable for in- and outdoor mid-term applications.

Particularly suitable for application on flat and slightly curved surfaces. No adhesive residue after removal, if correctly applied.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Available Colours

39 gloss 35 matt

Technical Data

Carrier: Monomeric PVC, highly stabilized,

calendered

Thickness: $70 \,\mu$ +/- $5 \,\%$

Adhesive: clear acrylic dispersion,

semi-permanent

Adhesion: 4 N/cm

Liner: one-sided clay-coated

silicone paper (120 g/m²)

Tensile strength md: >8,8 kN/m

Tensile strength cd: >5,0 kN/m

Application temperature: +10 - +40 °C

Temperature durability: -40 - +80 °C

Outdoor durability: 3-5 years

Standard Dimensions

1220 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

KEMICA S.r.I.

Via F.Ili Rusjan, 76 - Frazione Rupa 34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501 Fax: +39 0481 882 440 E-Mail: info@kemicasrl.it Internet: www.kemica.it 12/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.