



Applied to clear glass, the transparent Lime C film bestows a green tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating
M1



Storage From -5°C To +40°C
3 years



Reach Rohs Compliant
Respected



Widths Available
152cm

Construction

1. common scratch-resistant hard coat for durability and ease of maintenance when cleaning windows
2. High-quality polyester without optical distortion
3. PS adhesive, cures with glass within 15 days
4. adhesive protection liner, disposable after application

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

| | |
|--------------------------------------|---------------|
| Ultraviolet Transmission | 5% |
| Visible Light Transmission | 37% |
| Reflection Of External Visible Light | 8% |
| Reflection Of Internal Visible Light | 8% |
| Total Solar Energy Rejected | 32% |
| Total Solar Energy Rejected 2* | 29% |
| Solar Ratio : | |
| Solar Energy Reflection | 9% |
| Solar Energy Absorption | 43% |
| Solar Energy Transmission | 48% |
| Reduction In Solar Glare | 64% |
| G-Value | 0.69 |
| U-Value | 5.7 |
| Installation Type | Interior |
| Roll Length | 30.5 meters m |
| Film Composition | PET |
| Thickness | 40µ |
| Colour From The Outside | GREEN |

Installation Advice

Vertical position and standard glass surface*

| | |
|--------------------------------|---|
| Clear Single Pane | ✓ |
| Tinted Single Pane | ! |
| Reflective Tinted Single Pane | ✓ |
| Clear Double Pane | ✓ |
| Tinted Double Pane | ! |
| Reflective Tinted Double Pane | ✓ |
| Gas-Filled Double Pane - Low E | ✓ |
| Stadip Ext. Clear Double Pane | ✓ |
| Stadip Int. Clear Double Pane | ! |

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.