



Applied to clear glass, the Mat Green film bestows a mat green tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

### Certifications


**Warranty SOLAR SCREEN®**

5 years  
See the 'New guarantees for outdoor products' notice


**Fire-Resistance Rating**

M1


**Storage From -5°C To +40°C**

3 years


**Reach Rohs Compliant**

Respected


**Widths Available**

152cm

### Construction

1. Frosted polyester with satin surface
2. Bonding adhesive
3. High optical quality polyester
4. PS adhesive, glass polymerization within 15 days
5. Protection release liner, disposable after installation

### Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

### Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	45%
Reflection Of External Visible Light	8%
Reflection Of Internal Visible Light	8%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio :	
Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	58%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60µ
Colour From The Outside	GREEN

### Installation Advice

Vertical position and standard glass surface\*

Clear Single Pane	✓
Tinted Single Pane	!
Reflective Tinted Single Pane	✓
Clear Double Pane	!
Tinted Double Pane	!
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	!
Stadip Ext. Clear Double Pane	!
Stadip Int. Clear Double Pane	✗

✓ Yes ✗ Not Recommended ! Caution

\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.