

MAT YELLOW PET

Design

Mat coloured adhesive film



Applied to clear glass, the transparent Mat Yellow film bestows a mat yellow tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications



Warranty SOLAR SCREEN® 5 years See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available

Construction

- 1. Frosted polyester with satin surface
- 2. Bonding adhesive
- 3. High optical quality polyester
- 4. PS adhesive, glass polymerization within 15 days
- Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

Ultraviolet Transmission	1%
Visible Light Transmission	45%
Reflection Of External Visible Light	8%
Reflection Of Internal Visible Light	8%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio : Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	56%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	60μ
Colour From The Outside	YELLOW

Installation Advice

Vertical position and standard glass surface*

Clear Single Pane	✓
Tinted Single Pane	į
Reflective Tinted Single Pane	✓
Clear Double Pane	į.
Tinted Double Pane	į
Reflective Tinted Double Pane	✓
Gas-Filled Double Pane - Low E	į.
Stadip Ext. Clear Double Pane	į.
Stadip Int. Clear Double Pane	×

✓ Yes

X Not Recommended

Caution

Cautio

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.