



Applied to clear glass, the transparent Plum C film bestows a mauve tint to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

## Certifications



Warranty SOLAR SCREEN®
5 years
See the 'New guarantees for outdoor products' notice



Fire-Resistance Rating M1



Storage From -5°C To +40°C 3 years



Reach Rohs Compliant Respected



Widths Available

# Construction

- Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
- 2. Dyed polyester without optical distortion
- 3. PS adhesive, glass polymerization within 15 days
- 4. Protection release liner, disposable after installation

#### **Maintenance Instructions**

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

## **Technical Datasheet**

Ultraviolet Transmission	5%
Visible Light Transmission	34%
Reflection Of External Visible Light	8%
Reflection Of Internal Visible Light	8%
Total Solar Energy Rejected	32%
Total Solar Energy Rejected 2*	29%
Solar Ratio : Solar Energy Reflection	9%
Solar Energy Absorption	43%
Solar Energy Transmission	48%
Reduction In Solar Glare	60%
G-Value	0.69
U-Value	5.7
Installation Type	Interior
Roll Length	30.5 meters m
Film Composition	PET
Thickness	40μ
Colour From The Outside	MAUVE

### **Installation Advice**

Vertical position and standard glass surface\*

Clear Single Pane	<b>✓</b>
Tinted Single Pane	İ
Reflective Tinted Single Pane	<b>✓</b>
Clear Double Pane	İ
Tinted Double Pane	į.
Reflective Tinted Double Pane	<b>✓</b>
Gas-Filled Double Pane - Low E	į.
Stadip Ext. Clear Double Pane	İ
Stadip Int. Clear Double Pane	×

✓ Yes 

X Not Recommended 

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Caution

Cautio

\\*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.