



Applied to clear glass, the transparent Yellow C film bestows a yellow hue to the glass without diminishing its transparent properties. It is the perfect way to enliven any interior glazing (such as partitions, shower screens, etc.) with a touch of colour.

Certifications


Warranty SOLAR SCREEN®

5 years
See the 'New guarantees for outdoor products' notice


Fire-Resistance Rating

M1


Storage From -5°C To +40°C

3 years


Reach Rohs Compliant

Respected


Widths Available

152cm

Construction

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. Dyed polyester without optical distortion
3. PS adhesive, glass polymerization within 15 days
4. Protection release liner, disposable after installation

Maintenance Instructions

Soapy water solution (ref. 600-F0355 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Technical Datasheet

| | |
|--------------------------------------|---------------|
| Ultraviolet Transmission | 1% |
| Visible Light Transmission | 45% |
| Reflection Of External Visible Light | 9% |
| Reflection Of Internal Visible Light | 9% |
| Total Solar Energy Rejected | 22% |
| Total Solar Energy Rejected 2* | 25% |
| Solar Ratio : | |
| Solar Energy Reflection | 9% |
| Solar Energy Absorption | 18% |
| Solar Energy Transmission | 73% |
| Reduction In Solar Glare | 60% |
| U-Value | 5.7 |
| Installation Type | Interior |
| Roll Length | 30.5 meters m |
| Film Composition | PET |
| Thickness | 40µ |
| Colour From The Outside | YELLOW |

Installation Advice

Vertical position and standard glass surface*

| | |
|--------------------------------|---|
| Clear Single Pane | ✓ |
| Tinted Single Pane | ✓ |
| Reflective Tinted Single Pane | ✓ |
| Clear Double Pane | ✓ |
| Tinted Double Pane | ✓ |
| Reflective Tinted Double Pane | ✓ |
| Gas-Filled Double Pane - Low E | ✓ |
| Stadip Ext. Clear Double Pane | ✓ |
| Stadip Int. Clear Double Pane | ✗ |

✓ Yes ✗ Not Recommended ! Caution

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

The information on this data sheet is not binding; SOLAR SCREEN® reserves the right to change the composition of its products at any time. Please consult our warranty terms and general sales conditions.